



SOL 712" Fully Rugged tablet







IP65

MIL-STD-810H

MIL-STD-461G





1000 nits

5-foot Drop

- **◆ Intel® Core™ Ultra processors**
- Advanced display with high brightness and hyper dimming technology to adapt different ambient-light conditions
- WiFi 7 & 5G supported
- Dual hot-swap battery plus fast charging offers near indefinite capacity
- A wealth of I/O ports and expansion options fulfill field use
- MIL-STD 810H, MIL-STD 461G and IP65 certified





Specifications

System

◆ CPU : Arrow Lake Ultra 5 225U / Arrow Lake Ultra 7 255U

◆ Storage: 128 GB-1TB M.2 SSD ◆ Memory:DDR5 SO-DIMM 8-32GB

OS: Windows 11 GAC

Display

♦ 12" 2160 x 1440, 1000 nits high brightness

♦ 10-point Capacitive Touch supports glove touch with Gorilla Glass

 Capacitive multi-touch screen supports glove touch, water rejection, palm rejection, 2mm hard tip stylus

Communication

♦ BT5.4

♦ Wi-Fi 7 802.11be

♦ GNSS (GPS/ Glonass / BeiDou)

Optional 4G LTE/5G (Sub-6g)

Camera

◆ 2MP front camera, option 5MP hello camera

◆ 11MP auto focus rear camera with LED flash

Control Button

♦ Programmable button x 2

♦ Power, Volume, Windows button

Expansion Option

◆ 2D barcode reader (OCR option)

Fingerprint reader

Contactless Smart Card Reader

♦ FIDO2 NFC

UHF RFID

I/O Interface

◆ USB 3.2 Gen1 type A x 1
USB 3.2 type C x 2 (support Thunderbolt & charging)

◆ Speaker x 2 (front side)

◆ Audio jack (headphone/ microphone combo) x 1

♦ Sim slot x 1, eSim x 1

Docking connector x 1

Optional RF pass-through x 2

◆ RS-232 x 1 (available for option USB 2.0 / RJ45 / 2D barcode reader)

Security

♦ TPM2.0

Power

♦ USB-C AC adapter (65W, 100-240V AC, 50/60Hz)

• Fast charging supported

Standard: 3010 mAh, 11.4V, hot swappable

Rugged Feature

◆ IP65, MIL-STD-810H and MIL-STD-461G certified

♦ Vibration, shock and 5-foot drop resistance

Environmental

◆ Operating temperature : -20° C to +63° C¹

◆ Storage temperature : -30° C to +70° C

Humidity: 95%, non-condensing

Dimensions & Weight

♦ 304 x 209 x 23.9 mm (12" x 8.2" x 0.94") (W x H x D)

1.5kg (3.3lbs)

Software

◆ DashON, CamON, BioON, RuggOTA

1. This product is designed for non-charging operation in high ambient temperatures (up to +63°C/+145.4°F). In environments exceeding +50°C/+122°F, the product and nearby objects may become hot to the touch. Please avoid direct skin contact with hot surfaces. Specifications may change without prior notice.

